CA615K

THERMAL WELDING WORKS

Thermal leather glove, offers increased durability in the heavy industry

Specific benefits

📈 Performance

· Extra thick and long for extra protection of the entire arm
· The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- **Public works**
- **Building**
- **Finishing works / Craftsmanship**
- **Maintenance**
- **Automotive**
- **Mining**

Certifications and norms

CE

EN 388
3 1 3 2 X

EN 12477
TYPE A

EN 407
4 1 3 X 4 X

Protects against risks

Heat

CA615K
THERMAL WELDING WORKS
Thermal leather glove, offers increased durability in the heavy industry

Standards - Details

EN388:2016+A1:2018
3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
3 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

EN 407
THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
1 [0-4] CONTACT HEAT RESISTANCE
3 [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
4 [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Cut and sewn leather palm / leather back
Mechanical glove kind	Cut and sewn
Special gloves kind	Welding
Thickness (mm)	1,2 -> 1,4
Arm level protection	Forearm cuff (< 400mm)
Cuff caracteristic	Leather cuff
Benefits element	Kevlar stitching
Color	Red
Size	10
Type of packaging	Bulk bag of 12

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	🗁	⚖	Weight	Box Width	Box Depth	Box Height
CA615K10	Red	10	CA615K	3295249021597	13295249021594	60	12	22.1 kg	26.2 cm	37.0 cm	77.6 cm

🗁 Multiple sales

⚖ Minimum sales

▭ Box Width

▭ Box Depth

▭ Box Height